

(A Government of Kerala Undertaking) Thycaud P.O, Thiruvananthapuram - 14, Kerala. Tel: 0471 - 2945600, 2337353, Fax: 0471 - 2945647 Email :ep.kmscl@kerala.gov.in CIN: U24233KL200TSGC021616, PAN : AADCK4029M, GSTIN : 32AADCK4029M1ZK

Running Contract Details						
Equipment Name	Anesthesia Workstation					
Running Contract Valid Till	15-01-2026					
Tender Ref No	KMSCL/EP/T512/2/2023					
Tendered Quantity	80					
Supplier Name	M/s Sree Gokulam Healthcare Pvt Ltd					
GST No	32AAJCS3502K1ZI					
Installation & Delivery Period	8 Week(s)					
Up-time / PM vist	95% & 4 Visits per year					
Warranty period	3 Years					

Supplier`s Details								
Address	Contact Details							
Sree Gokulam Healthcare Pvt. Ltd. Door No. 36/2535A	Contact Person	Anoop						
Kunnumpuram Junction Edappally North PO.	Phone							
Kochi- 682024	Mobile No	9995813333						
	Email	sales@gokulamhealthcare.com						

Item-wise Price Details													
#	Item Details			Unit Rate (Incl.all taxes & charge	Service C (Through K	-	Grand Total						
1	Anesthesia Workstation Model & Make : WATO EX 35/ Shenzhen Mindray Bio -Medical Electronics Co. Ltd				104832 Incl.GST : 1		77313.6	1125633.6					
2	Iso Flurane Vaporizer			8624 Incl.GST : 1		6360.2		92600.2					
3	Sevo Flurane Vaporizer				8624 Incl.GST : 1		6360.2		92600.2				
				122080	00	90034	1310834						
Annual / Comprehensive Maintenance Charges (Exl.Tax)													
Rate	9	4 th Year	5 th Year	6 th Year	7 th Year	8 th Year	9 th Year		10 th Year				
	Anesthesia Workstation												
Labou	Labour 35,000.00 35,000.00 35,000.0		0 35,000.00	35,000.00	35,000.00		35,000.00						
Comp ve	rehensi	79,600.00	83,580.00	87,759.0	0 92,145.00	96,755.00	1,01,590.00		1,06,670.00				

Other terms & conditions

1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).

2. The supplier shall submit performance security amounting to 5.00% of the value of the supply order.

3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.

4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).

5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

Technical Specification

Equipment : Anesthesia Workstation

Equipment: Anesthesia Work Station

- 1. The workstation should have a built-in anesthesia ventilator with pressure, volume controlled SIMV, Pressure support with Apnoea backup and spirometry.
- 2. t should be electronically controlled, Pneumatically operated / electrically driven
- 3. Should provide with adult and paediatric reusable and autoclavable light weight tubing breathing circuit.
- 4. Should be able to deliver a tidal volume from 20ml to 1500ml. Peak flow without fresh gas flow should be minimum 110L/min.
- 5. Should have a battery backup for at least 1 hr with low battery alarm and over charge protection.
- 6. Should have monitoring facility of airway pressure, tidal volume, frequency, oxygen concentration and AGM with modular integration.
- 7. Should have touch screen display of at least 10 inches for set parameters and graphical display for measured parameters
- 8. Should have automatic self test plus automatic and manual leak test..
- 9. Anaesthesia machine should be with 3 gas supply system (O2, N2O, Air) with pipeline connections and reserve cylinder yokes.
- 10. Gas cylinder (pin indexed) yokes with sturdy clamping bars for easy handling.
- 11. Should supply pin index yokes for connecting cylinders for O2-1No, N2O 1No and 1no for Air through pipeline.
- 12. Should have pressure measurements for all gas inlets including central lines mounted on the front panel for easy visibility.
- 13. Should have audible and visual alarm for major events
- 14. Oxygen and Nitrous oxide should be linked either mechanically or pneumatically to ensure a minimum of 25% oxygen delivery at all times to avoid delivery of hypoxic mixture.
- 15. Should have dual cascade/ virtual type flow meter for O2 and N2O and air calibrated in multiple scale.
- 16. The anaesthesia machine should have a master control $\ensuremath{\text{ON/OFF}}$ switch.
- 17. Provision to mount any two selected vaporizer of the same manufacturer with interlocking facility to allow use of only one vaporizer at a time.
- 18. Iso and sevoflurane vaporizer of newer generation having specifications equivalent to tech 7 type to be provided.
- 19. Non-return cum pressure relief valve when pressure exceeds 120cmof H2O.
- 20. Should have only one common gas outlet (ACGO) and auxiliary O2 Outlet with flow meter.
- 21. Should provide with oxygen flush switch.
- 22. Circle absorber with heated manifold / some inbuilt mechanism to remove water condensation. It should be autoclavable by dismantling without help of any tools. It should be with ventilator selector switch and circle on/off switch. Should have an automatic Co2 bypass.
- 23. Should have low flow anaesthesia technique with tidal volume and fresh gas flow compensation.
- 24. Should have a facility to connect the passive scavenging system
- 25. Should have safety certificate from a competent authority CE issued by a notified body registered in the European commission / FDA (US)/ STQC CB Certificate/ STQC S Certificate or valid detailed electrical and functional safety test report from ERTL. Copy of the certificate/ test report shall be produced along with the technical bid

- 26. Should have a provision for mounting monitors with minimum 3 drawers.
- 27. Should have antistatic wheels and Foot brakes.
- 28. Should supply with Standard bains circuit 2nos, Adult and pediatric Reusable circuit 2nos each, JR Circuit (Reusable)-1 No, Limbo Circuit(disposable)- 5 Nos and HME filters-25 Nos. The circuits shall be of Anaesthetics/ Flexicare/ Neon make/ Standard manufacturer.
- 29. Reservoir bag (500ml, 1 litre, 1.5 litre and 2liters):-2 nos.each along with the machine.
- 30. Connectors for bains circuit: 5 nos with each machine.
- 31. AMBU bag(adult&pediatric): 1 no each along with the machine. It should be autoclavable.
- 32. Pressure regulated valve with 5 meter hose and connector (conversion kit) for oxygen and N2O should be provided with each machine 1 each.
- 33. Should be supplied with driver gas hoses with necessary attachments (colour coded).
- 34. Should work in 220-240Vac 50 Hz input supply.
- 35. Should have inbuilt Electrical outlets of minimum 3nos with switches/ circuit Brakers
- 36. Should supply with automatic servo stabilizer of suitable capacity
- 37. The Anaesthesia machine, ventilator and vaporizer should be from the same manufacturer
- 38. Should have Medical grade IP44 or above rated power cord to match D-Type plug. The protective earthling resistance (PER) and leakage current (LC) values should be as per IEC 62353/AAMI/NFPA-99.
- 39. Battery, O2 Cell and flow sensor should be covered under warranty as well as CAMC.
- 40. Should be supplied with medisorb or equivalent for circle absorber (4 kg)

Note:

- 1. If CDSCO (Central Drugs Standard Control Organization) certification is required for the import and marketing of the equipment, then the same shall be submitted along with the technical bid
- 2. Warranty exclusions if any shall be discussed at the time of prebid meeting else the tender condition as per clause 6.31.20 shall prevail