



<b>Running Contract Details</b>	
Equipment Name	HOSPITAL FURNITURE
Running Contract Valid Till	21-03-2024
Tender Ref No	KMSCL/EP/T414/328/2021
Tendered Quantity	200
Supplier Name	M/s Parin Furniture Limited
GST No	24AAECP1870C1ZT
Installation & Delivery Period	6 Week(s)
Up-time / PM vist	95% & 0 Visits per year
Warranty period	1 Years

<b>Supplier`s Details</b>		
<b>Address</b>	<b>Contact Details</b>	
	Contact Person	
	Phone	
	Mobile No	
	Email	

<b>Item-wise Price Details</b>				
#	Item Details	Unit Rate (Incl.all taxes & charges)	Service Charges (Through KMSCL)	Grand Total
1	<b>Executive chair with arm rest</b> <i>Model &amp; Make : PC-1</i>	5608.99 Incl.GST :18%	392.63	6001.62
		<b>5608.99</b>	<b>392.63</b>	<b>6001.62</b>

### **Other terms & conditions**

1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).
2. The supplier shall submit performance security amounting to 5.00% of the value of the supply order.
3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.
4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).

5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

## **Technical Specification**

### **Equipment :Executive chair with arm rest**

â€

1. Back: (W) 49.0 cm x (H)71.0Cm,
2. Seat : (W) 49.0 cm x (D) 44.0 cm
3. Overall Dimensions of Chair : Seat Height - min 41.0 to max 53.0cm, Height - min 100.0 to max 112.0cm.
4. Width & Depth of Chair as measured from pedestal - Width-76.3 cm and Depth-76.3 cm.
5. The seat and back shall be made up of 1.2+/-0.1cm thick hot pressed plywood measured as per QA method described in OCP-QLTA-P14-18 and upholstered with fabric and moulded polyurethane foam with PVC lipping all around.
6. The moulded polyurethane foam shall be of density  $45\pm 2\text{kg/m}^3$ , and hardness load  $16\pm 2\text{kgf}$  as per
7. The dimensions of seat shall be- 49.0cm(W) x 44.0cm(D) and of back shall be 49.0cm(W) x 71.0cm(H).
8. The one-Piece armrests should made of black integral skin polyurethane with 50-70 shore 'A' Hardness and reinforced with M.S insert.
9. The armrests shall be scratch and weather resistant.
10. The armrests shall be fitted to the seat with seat/armrest connecting strip assembly made of  $0.5\pm 0.05\text{cm}$  thick HR steel.
11. The mechanism of the chair shall have following facilities
  - a.  $360^\circ$  revolving type, Center tilt synchro mechanism,
  - b. Tilt tension adjustment, Upright position locking
  - c. 17 degree+2maximum tilt on pivot center.
12. The chair shall be provided with pneumatic height adjustment which shall have stroke of  $12.0\pm 0.3\text{ cm}$ .
13. The bellow should be 3 piece telescopic type and injection moulded in black polypropylene.
14. The pedestal shall be injection moulded in black 33% glass-filled Nylon-66.
15. It shall be fitted with 5 Nos twin wheel castor.
16. The size of the pedestal shall be  $66.3\pm 0.5\text{ cm}$  pitch-centre-dia  $76.3\pm 1.0\text{ cm}$  with castors
17. The twin wheel castors shall be made black nylon. Dimensions Tolerance/ variations shall be within  $\pm 1\text{ cm}$ .
18. should have metal base frame.