



Running Contract Details	
Equipment Name	Bed Side Locker
Running Contract Valid Till	21-03-2024
Tender Ref No	KMSCL/EP/T422(R)/424/2021
Tendered Quantity	5000
Supplier Name	M/s Kerala Surgical Equipment Co
GST No	32AACFK7295D1ZG
Installation & Delivery Period	6 Week(s)
Up-time / PM vist	95% & 0 Visits per year
Warranty period	1 Years

Supplier`s Details		
Address	Contact Details	
No.41/1737 A MES Centre Near Town Hall Banerji Road Cochin -18	Contact Person	Mr. Abbas
	Phone	
	Mobile No	9539012460
	Email	info@keralasurgicals.com

Item-wise Price Details				
#	Item Details	Unit Rate (Incl.all taxes & charges)	Service Charges (Through KMSCL)	Grand Total
1	<b>Bed Side Locker</b> <i>Model &amp; Make : Medik-195</i>	5546 Incl.GST :18%	388.22	5934.22
		<b>5546</b>	<b>388.22</b>	<b>5934.22</b>

### **Other terms & conditions**

1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).
2. The supplier shall submit performance security amounting to 5.00% of the value of the supply order.
3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.
4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).

5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

## **Technical Specification**

### **Equipment :Bed Side Locker**

1. overall dimensions should be 400W x 420 D x 840mm H
2. The Locker should have one drawer unit and one cabinet unit fitted with Cam lock.
3. A Gap should be provided between the drawer and Cabinet unit for storage.
4. The locker top should be of 0.8mm thick SS 304 Grade sheet.
5. The SS sheet should be finished in buff-matt finish.
6. The top should have raised border of 10mm height on three sides.
7. Drawer should be made 1 mm thick CRCA sheet and it should be fitted with ball slides for smooth drawer movement and also a recess to serve as handle.
8. Cabinet should made 1 mm thick CRCA sheet, fitted with hinge door and lock and should have louvers for ventilation.
9. Back of the locker should be provided with vertical spacer made of nylon with uniformly distributed total load bearing capacity of 20 kg.
10. Test certificates of these tests should be available proof loading test , cycle tests, impact test, salt spray test, castor break test.
11. Should be GREENGUARD / SGS & BIFMA/ANSI certified.
12. The manufacturer should compliant with ISO 9001, 14001, 13485 & OHSAS 18001.