KERALA MEDICAL SERVICES CORPORATION LTD



(A Government of Kerala Undertaking) Thycaud P.O, Thiruvananthapuram - 14, Kerala. Tel: 0471 - 2945600, 2337353, Fax: 0471 - 2945647

Email:engg_ep@kmscl.kerala.gov.in

CIN: U24233KL200TSGC021616, PAN: AADCK4029M, GSTIN: 32AADCK4029M1ZK

Running Contract Details			
Equipment Name	HOSPITAL FURNITURE		
Running Contract Valid Till	21-03-2024		
Tender Ref No	KMSCL/EP/T414/328/2021		
Tendered Quantity	2000		
Supplier Name	M/s STAR CHAIRS		
GST No	32ALMPP7869B1ZT		
Installation & Delivery Period	6 Week(s)		
Up-time / PM vist	95% & 0 Visits per year		
Warranty period	1 Years		

Supplier`s Details					
Address	Contact Details				
Andaparambu	Contact Person	BIiju Poulose			
Anjur Mundur.P.O	Phone	4872212969			
Thrissur 680541	Mobile No	9495567070			
	Email	info@starchairs.com			

Item-wise Price Details						
#	Item Details	Unit Rate (Incl.all taxes & charges)	Service Charges (Through KMSCL)	Grand Total		
1	IV Stand (Drip stand) Model & Make : SC IVS 001	2183 Incl.GST :18%	152.81	2335.81		
		2183	152.81	2335.81		

Other terms & conditions

- 1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).
- 2. The supplier shall submit performance security amounting to 5.00% of the value of the supply order.
- 3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.
- 4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).

5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

Technical Specification

Equipment :IV Stand (Drip stand)

1.Strong SS tubular construction mounted on five pronged sturdy base fitted with five swivel castors, 50mm dia. Atleast 2mm thickness.

2. SS rod with four hooks, height adjustable from approx. 1620 mm to 2340mm