

(A Government of Kerala Undertaking) Thycaud P.O, Thiruvananthapuram - 14, Kerala. Tel: 0471 - 2945600, 2337353, Fax: 0471 - 2945647 Email :ep.kmscl@kerala.gov.in CIN: U24233KL200TSGC021616, PAN : AADCK4029M, GSTIN : 32AADCK4029M1ZK

Running Contract Details						
Equipment Name	Ventilator Non invasive					
Running Contract Valid Till	17-02-2025					
Tender Ref No	KMSCL/EP/T399/136C/2021					
Tendered Quantity	500					
Supplier Name	M/s Air Liquid Medical Systems Pvt Ltd					
GST No	33AAACE8420F1Z3					
Installation & Delivery Period	8 Week(s)					
Up-time / PM vist	95% & 4 Visits per year					
Warranty period	3 Years					

Supplier`s Details								
Address	Contact Details							
5th Floo Tower B	Contact Person	Mahesh						
Campus Tek Meadows No 51 Rajiv Gandhi Salai Sholinganallur	Phone							
Chennai - 600119	Mobile No	9895019008						
	Email	airliquideservice@gmail.com,mahesh.m@air liquide.com,sharmi.kishore@airliquide.com, sales.ecss@airliquide.com						

Item-wise Price Details													
#	# Item Details				Unit Rate (Incl.all taxes & charge		Service Charges (Through KMSCL)		Grand Total				
Ventilator Non invasive Model & Make : MONNAL T75/AIR LIQUIDE					80080 Incl.GST : 12		59059	859859					
					80080	00	59059		859859				
Annual / Comprehensive Maintenance Charges (Exl.Tax)													
Rate		4 th Year	5 th Year	6 th Year	7 th Year	8 th Year	9 th Year		10 th Year				
	Ventilator Non invasive												
Labour	r	40,000.00	42,000.00	44,100.00	46,305.00	48,620.00	51,05	51.00	53,604.00				
Compr ve	ehensi	60,000.00	63,000.00	66,150.00	69,458.00	72,930.00	76,57	77.00	80,406.00				

Other terms & conditions

1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).

2. The supplier shall submit performance security amounting to 3.00% of the value of the supply order.

3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.

4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).

5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

Technical Specification

Equipment : Ventilator Non invasive

- 1. Should have Accurate Delivery and Automatic control of CPAP pressure over the complete range of pressure (4-20 cm H2O) and Flow (0 to 200 LPM).
- 2. Should have color LCD touch screen of at least 10 inches size for easy access and visibility.
- 3. Should have patient effort indication with low respiratory rate alarm.
- 4. Should have Inbuilt Air Oxygen Mixer for the required level of FiO2.
- 5. Fio2 settings: 21-100%.
- 6. Should have the following alarms
- a. Air / Oxygen Failure
- b. Low O2 supply
- c. Low & high respiratory rate
- d. Circuit Open/disconnect alarm
- e. High / Low Flow Rate.
- f. Low& high tidal volume
- g. Low& high inspiratory pressure
- 1. Bi-PAP with full face/nasal mask
- 2. Should have two pressure levels of EPAP from 4-20 cm of H2O & IPAP from 4 40 cm of H2O
- 3. Should be able to set the frequency of 4 40 bpm
- 4. S / T : 4 40 cm of H2O
- 5. Fast response time, 20 milliseconds.
- 6. Leak compensation up to 60 liters/min
- 7. Settings: FiO2, EPAP, IPAP
- 8. Rise time should be adjustable
- 9. I:E ratio/ I time: adjustable
- 10. Modes: CPAP, S/T, Pressure controlled, Volume assured pressure support. Also should have ramp and flex settings in CPAP mode
- 11. Flow vs Time, Pressure vs Time and Volume vs Time graphs. Monitoring parameters: Rate, PIP, leakage, tidal volume, minute volume.
- 12. Should have a display of set and measured parameters
- 13. Supplied with dedicated patient circuit (adult).
- 14. Should have inbuilt soundless compressor/blower/turbine
- 15. Should have settable/automatic trigger sensitivity
- 16. Should be supplied with the following
- a. Small, medium & large masks -5nos each
- b. Patient circuit-5nos.
- 1. Should work with input 200 to 240Vac 50 Hz supply.
- 2. Should have an inbuilt battery backup of at least 1hrs.

- 3. Equipment should be trolley mounted and should be supplied along with the equipment
- 4. Should have a safety certificate from a competent authority CE issued by a notified body registered in European Commission / FDA (US) / STQC CB certificate / STQC S certificate or valid detailed electrical and functional safety test report from ERTL. Copy of the certificate/test report shall be produced along with the technical bid.
- 5. High Flow Therapy with Flow range 0 60LPM