



Running Contract Details	
Equipment Name	Revolving Chair
Running Contract Valid Till	21-03-2024
Tender Ref No	KMSCL/EP/T416/429/2021
Tendered Quantity	10000
Supplier Name	M/s Naran Chirakkal Corporate Private Ltd
GST No	32AAF0424R1ZQ
Installation & Delivery Period	6 Week(s)
Up-time / PM vist	95% & 0 Visits per year
Warranty period	1 Years

Supplier`s Details		
Address	Contact Details	
12/768D - Kozhikode Bypass Pantheeramkavu Kerala - 673019	Contact Person	JilbinStephen
	Phone	
	Mobile No	9947273331
	Email	adminclt@bosqindia.com

Item-wise Price Details				
#	Item Details	Unit Rate (Incl.all taxes & charges)	Service Charges (Through KMSCL)	Grand Total
1	<b>Revolving Chair</b> <i>Model &amp; Make : BOSQ-REVOLVING CHAIR</i>	5983.99 Incl.GST :18%	418.88	6402.87
		<b>5983.99</b>	<b>418.88</b>	<b>6402.87</b>

### **Other terms & conditions**

1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).
2. The supplier shall submit performance security amounting to 5.00% of the value of the supply order.
3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.
4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).

5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

## **Technical Specification**

### **Equipment :Revolving Chair**

1. The seat and back should be made up of  $1.2 \pm 0.1$ cm thick hot-pressed plywood measured as per QA method described in OCP-QLTA-P14-18 and upholstered with fabric upholstery covers and moulded Polyurethane foam.
2. The back foam should be designed with contoured lumbar support for better comfort.
3. The seat should be extra thick foam on front edge to give comfort to popliteal area.
4. The dimensions of back should be 47 cm(W) x 65 cm(H) and of seat should be 46.0 cm (W) x 47.0 cm (D- lumbar point to seat edge).
5. The High resilience polyurethane foam should be moulded with density not less than 45 kg/m<sup>3</sup>.
6. The one-piece armrests should be injection moulded from black Polypropylene.
7. The mechanism should be designed with 360° revolving type, Upright-position locking, Tilt tension adjustment, Seat/back tilting ratio of 1:3. The pneumatic height adjustment should have an adjustment stroke of  $12.0 \pm 0.5$ cm. The bellow should be 3 piece telescopic type and injection moulded in black Polypropylene.
8. The pedestal should be injection moulded in black 33%glass-filled Nylon-66 and fitted with 5 nos. twin wheel castors.
9. The pedestal should be  $66 \pm 0.5$ cm. pitch-center dia. ( $76.3 \pm 1.0$ cm with castors). The twin wheel castors should be injection moulded in Black Nylon.
10. Overall Dimensions (approx) of Chair should be Seat Height - min 42 to max 54cm, Height - min 97.0 to max 109.0cm, Width & Depth of Chair as measured from pedestal - Width-76 cm and Depth-76 cm.
11. Should be GREENGUARD / SGS & BIFMA/ANSI certified.
12. The manufacturer should be ISO certified.