KERALA MEDICAL SERVICES CORPORATION LTD



(A Government of Kerala Undertaking) Thycaud P.O, Thiruvananthapuram - 14, Kerala. Tel: 0471 - 2945600, 2337353, Fax: 0471 - 2945647

Email:ep.kmscl@kerala.gov.in

CIN: U24233KL200TSGC021616, PAN: AADCK4029M, GSTIN: 32AADCK4029M1ZK

Running Contract Details			
Equipment Name	Dry Bath		
Running Contract Valid Till	27-06-2026		
Tender Ref No	KMSCL/EP/T521/315/2024		
Tendered Quantity	25		
Supplier Name	M/s AASTMEDI TECH PRIVATE LIMITED		
GST No	32AATCA5385Q1ZT		
Installation & Delivery Period	8 Week(s)		
Up-time / PM vist	95% & 0 Visits per year		
Warranty period	1 Years		

Supplier`s Details					
Address	Contact Details				
Door No 16/365 16/366 16/367	Contact Person	Prasanth G Pillai			
Sreevihar Pallarimangalam Olakkettyambalam P.O. Mavelikara	Phone	8589019182			
	Mobile No	9567859180			
	Email	info@astmeditech.com			

	Item-wise Price Details					
#	Item Details	Unit Rate (Incl.all taxes & charges)	Service Charges (Through KMSCL)	Grand Total		
1	<b>Dry Bath</b> Model & Make : DDI 24/AAST MEDITECH	26432 Incl.GST :18%	1850.24	28282.24		
		26432	1850.24	28282.24		

## **Other terms & conditions**

- 1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).
- $2. \ The \ supplier \ shall \ submit \ performance \ security \ amounting \ to \ 5.00\% \ of \ the \ value \ of \ the \ supply \ order.$
- 3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.
- 4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).

5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

# **Technical Specification**

## **Equipment: Dry Bath**

### **Equipment: Dry Bath**

- 1. Temperature range: ambient to 110 degree C. Controlled to +/- 0.2 deg. C (or better) by Solid State Time Proportional Temperature Controller.
- 2. Digital-Display using PT-100 Sensor
- 3. Should be supplied with 3 Nos. interchangeable and autoclavable anodized aluminium blocks of 75x50x50 mm size for accommodating 0.5 ml, 1.5 ml tubes
- 4. 12mm, 16mm or 19mm test tubes or two block of 150x75x50 mm size for accommodating 100 Tubes of 10mm Diameter
- 5. The body made of heavy M.S. and painted with epoxy powder paint.
- 6. All accessories needed to make the equipment functional, must be supplied