

Running Contract Details	
Equipment Name	MATERIAL TROLLEY VARIOUS TYPES
Running Contract Valid Till	05-12-2026
Tender Ref No	KMSCL/EP/T456/1609A/2022
Tendered Quantity	Item wise mentioned in below
Supplier Name	M/s GANGOTHRI INDUSTRIES
GST No	32BIQPM4664R1ZD
Installation & Delivery Period	6 Week(s)
Up-time / PM vist	95% & 0 Visits per year
Warranty period	1 Years

Supplier`s Details		
Address	Contact Details	
MLA Road Nellipanathazham Chevayur P.O Kozhikode-673017	Contact Person	Sunil Kumar
	Phone	
	Mobile No	9539036566
	Email	gangothriindustrials@gmail.com

Item-wise Price Details					
#	Item Details	Tendered Qty	Unit Rate (Incl.all taxes & charges)	Service Charges (Through KMSCL)	Grand Total
1	Material Trolley Type III (0.90m(L) x 0.60m(B) x 1.00m(H)) <i>Model & Make : 1609/Gangothri</i>	100	22078.98 Incl.GST :18%	1545.53	23624.51
			22078.98	1545.53	23624.51

Other terms & conditions

1. The supplier shall execute an agreement with the purchaser as per tender conditions (agreement format is given in the tender document).
2. The supplier shall submit performance security amounting to 5.00% of the value of the supply order.
3. The labour & comprehensive charges of equipment after the completion of warranty period is finalized by KMSCL as mentioned above.
4. Since discount rate is not applicable for equipment under Running Contract of KMSCL, purchase/supply order can be issued directly

to supplier at the given rate with tax & other charges (exclusive of KMSCL service charges).

5. If purchase/supply order is issued directly to the supplier, KMSCL service charge need not be paid. But the copy of the said order may be forwarded to KMSCL for information.

Technical Specification

Equipment :Material Trolley Type III (0.90m(L) x 0.60m(B) x 1.00m(H))

1. Should have heavy duty material movement trolley of including with two side handle with angles.
2. Frame work should have 16 Gauge GI Sheet and GI Tube.
3. Should have heavy duty wheels (8INCH) , 4 numbers with bearing, Material PU.
4. Loading capacity should have approximately 800KG.
5. Should have fully powder coated material.
6. Should have extra support at the bottom of the platform for more stability.